6

CLAIMS:

1.   A record carrier comprising synchronization patterns for identifying blocks of
information, said synchronization patterns comprising a part for distinguishing one such
synchronization pattern from another such synchronization pattern, characterized in that the
part for distinguishing the synchronization patterns consists of the bit sequence **100 101** or of
5   the bit sequence **010 101**.

2.   Record carrier according to claim 1, characterized in that the synchronization
pattern comprising a part for distinguishing the synchronization patterns consisting of the bit
sequence **100 101** or of the bit sequence **010 101**, is directly followed by a bit sequence not
10   violating the Repeated Minimum Transition Runlength constraint.

3.   Record carrier according to claim 2, characterized in that the synchronization
pattern comprising a part for distinguishing the synchronization patterns consisting of the bit
sequence **100 101** or of the bit sequence **010 101**, is directly followed by any 8 bit data bit
15   sequence except the sequence **01 11 01 11**.

4.   A record carrier comprising synchronization patterns for identifying blocks of
information, said synchronization patterns comprising a part for distinguishing one such
synchronization pattern from another such synchronization pattern, characterized in that the
20   part for distinguishing the synchronization patterns consists of the bit sequence **101 001**, or
the bit sequence **010 100**, or the bit sequence **100 100.**

5.   A device for recording synchronization patterns for identifying blocks of
information onto a record carrier, said synchronization patterns comprising a part for
25   distinguishing one such synchronization pattern from another such synchronization pattern,
characterized in that the device is operative for recording synchronization patterns
comprising a part for distinguishing the synchronization patterns which consists of the bit
sequence **100 101** or of the bit sequence **010 101**.

6.   A device for recording synchronization patterns for identifying blocks of
information onto a record carrier, said synchronization patterns comprising a part for
distinguishing one such synchronization pattern from another such synchronization pattern,
characterized in that the device is operative for recording synchronization patterns

5   comprising a part for distinguishing the synchronization patterns which consists of the bit
sequence **101 001**, or the bit sequence **010 100**, or the bit sequence **100 100**.

7.   A device for retrieving data patterns from a record carrier, said data patterns
comprising synchronization patterns for identifying blocks of information, said

10   synchronization patterns comprising a part for distinguishing one such synchronization
pattern from another such synchronization pattern, characterized in that the device is
operative for identifying a synchronization pattern comprising a part for distinguishing the
synchronization patterns which consists of the bit sequence **100 101** or of the bit sequence
010 101.

15

8.   A device for retrieving data patterns from a record carrier, said data patterns
comprising synchronization patterns for identifying blocks of information, said
synchronization patterns comprising a part for distinguishing one such synchronization
pattern from another such synchronization pattern, characterized in that the device is

20   operative for identifying a synchronization pattern comprising a part for distinguishing the
synchronization patterns which consists of the bit sequence **101 001**, or the bit sequence **010
100**, or the bit sequence **100 100**.